

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
30 June 2005 (30.06.2005)

PCT

(10) International Publication Number
WO 2005/059434 A1

(51) International Patent Classification⁷: **F21V 8/00**

(21) International Application Number:
PCT/GB2004/005111

(22) International Filing Date: 7 December 2004 (07.12.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0329205.9 17 December 2003 (17.12.2003) GB

(71) Applicant and

(72) Inventor: **GRAHAM, Morton** [GB/GB]; 5 Parkway,
West Houghton, Bolton, Lancashire BL5 2RY (GB).

(74) Agent: **HARRISON GODDARD FOOTE**; Orlando
House, 11c Compstall Road, Marple Bridge, Stockport
SK6 5HH (GB).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,

CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:


— of inventorship (Rule 4.17(iv)) for US only

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: AN ILLUMINATION DEVICE



(57) Abstract: An illumination device comprising an elongate rod (10) or strip of translu-
cent material located within a tube (11) to define a gas space (12) therebetween, the rod
having a disrupted surface by way of undulation (13) or striation (17), and a light source
located at one or both ends of the device to cause light travelling along the rod to exit
transversely to its axis. Primary diffusion occurs within the rod by total internal reflection.
Secondary diffusion occurs within the gas space, and a substantially uniform light output is
generated by the surrounding tube. For longer lengths of rod the striation may be increased
within a central region (21, 22) thus to ensure uniformity of light output throughout the
length. If required, a beam of light may be generated by providing a reflector (15, 16)
within the gas space (12).



WO 2005/059434 A1